DESMONUSA
Professional Refrigeration

9731 NW 114th WAY Miami, FL. 33178
Office: (305) 883-5581 Fax: (305) 883-4651
www.desmon-usa.com

Project Name: _____

Location: _____

Item #: _____ Qty: _____

AIA #

SIS #

MODEL: GM14G GOLD SERIES Double Glass Door Cabinet Cooler

- The Desmon GOLD line provides products completely manufactured with stainless steel AISI 304 with a monobody structure with a finely satined extern (Scotch-Brite).
- The floor is stamped and has rounded corners, for ease of cleaning and long life.
- The insulation thickness is 2 3/8" of high density polyurethane, which is HCFC free for the protection of the environment.
- Brand-new digital controller with H.A.A.C.P. standard.
- The refrigeration fluid is R404a, which saves energy by being highly efficient.
- The access to the refrigeration system is made easy by a hinged cover.
- The doors are with a magnetic self-closing system, with the largest opening 180º, with a door lock at 105º.
- All the refrigerated cabinets are provided with an internal light and lock.
- The internal guides are a “C” shape to allow for easy removal of the grills and they are anti-turnover. The shelves are stainless steel and are adjustable at 2" intervals.

Model #	Classification	Refrigerant	Volts / HZ	Phase	Full Load Amps	Temp (F)	Dimensions (Inch)			Packing Dimensions (Inch)		
							W	D	H	W	D	H
GM14G	Beverage Cooler	R404A	115 / 60	1	14	+28 to +46	56 1/2	31 1/2	82 1/2	58 1/4	33	88

HP	Doors	Shelves	Guides	Weight	Cubic
1/2	2	6	12	(lbs) 518	(ft) 49

Notes
- Specification subject to change without notice.
- Chart dimensions rounded up to the nearest 1/8".

Warranty
- Two year warranty on all parts and labor and an additional
- three year warranty on the compressor. (U.S.A. only)

Printed in U.S.A.
12/08