

PRIMA



PRIMA delivers the benefits of FBM's continuous tempering technology to demanding confectioners and chocolatiers who need an enrobing attachment but who work in very small batches and whose production is measured in hundreds of kilos per week, not per day. *Prima is the smallest continuous tempering machine on the market that accepts an enrobing attachment.*

The continuous tempering cycle in **Prima** is controlled by a custom-programmed dedicated CPU that monitors and adjusts heating and cooling automatically within a very narrow range based on the set melting and tempering points. The working bowl is heated by thermoelectric induction and the tempering pipe is cooled directly by the refrigerant gas, delivering fast response times, precise control, and reduced energy consumption.

The auger in the Prima's tempering pipe can be eversed to empty it, reducing the amount of time required to restart the tempering cycle or to change chocolate. A removable auger for cleaning is a standard feature, as is a pedal-operated electronic depositor with user-selectable time and repetitions (up to 9) for filling molds and other uses.

STANDARD FEATURES:

- Removable vibrating table (heated by working bowl)
- Night cycle
- Removable/reversible tempering auger
- Pedal-operated electronic depositor with user-selectable time and repetitions
- Swiveling casters

ENROBING ATTACHMENT FEATURES:

- Overall length: 1.045m
- One piece in 3 sections; stainless steel entrance and enrobing sections, food-contact-safe take-off belt
- Usable width 180mm
- Speed regulator
- Equipped with net beater/shaker, independent motor for de-tailer, adjustable air blower

SPECIFICATIONS:

- Capacity (bowl): 7kg (~15.5 pounds)
- Throughput: 3-5x bowl capacity per hour, depending on the type of work being done
- Installed power: 800 watts (900 w/ enrober) @ 220V single-phase
- Dimensions: 380(w) x 400(d) x 1200(overall height); working plane @ 860mm; vibrating table 410(w) x 300(d)
- Weight: ~90kg (~200 lbs)

PRICING:

CAT#. 14987	220V 3-phase 60 Hz	€ 6,650
CAT#. 15475	220V single-phase 60 Hz (includes auger inverter)	€ 7,300
CAT#. 13375	Enrobing attachment	€ 4,500
	Oversize vibrating table (replaces standard vibrating table).....	€ 250
	<i>120V operation for #15475 requires separate 120V>220V voltage converter</i>	
	220 / 380V 50 Hz 3-phase	POA
Crating:	Pallet / Wooden cage	€ 25 / 100